

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently amended) A form panel for placing concrete made of plastic comprising:  
a hollow sheathing section, one side of which forms a concrete placing surface,  
[[and]]

hollow side panel sections bent out at right angles from both ends of said sheathing section on a side of said sheathing section opposite to said concrete placing surface,

wherein two hollow projecting sections, which extend in a vertical direction,  
[[are]] provided on ends of an outside surface of at least one of said hollow side panel sections in  
a protruding manner toward the outside of said hollow side panel sections, each of said two hollow projecting sections having a length side[[s]] surface and two width side[[s]] surfaces,  
wherein one of said width side surfaces of one of said two hollow projecting sections provided on said sheathing section, which is on said concrete placing surface of said sheathing section and is coplanar with said concrete placing surface of said sheathing section,

a first diagonal rib which is diagonal relative to said concrete placing surface [[is]]  
formed within said one of said two hollow projecting sections, wherein one of said two width side surfaces of [[which]] said one of said two hollow projecting sections provided with said first diagonal rib is coplanar with said concrete placing surface of said sheathing section provided on said sheathing section, and in contact with a corner, which is located on a distal end of said one of

said two hollow projecting sections on said concrete placing surface of said sheathing section, and  
a second diagonal rib which is diagonal relative to said concrete placing surface  
[[is]] formed within the other of said two hollow projecting sections, wherein one of two width  
side surfaces of said the other of said two hollow projecting sections provided with said second  
diagonal rib is provided at a distal end surface of said hollow side panel section, which is on the  
opposite side of the hollow sheathing section, and said second diagonal rib is in contact with a  
corner, which is located on a distal end of said the other of two hollow projecting sections on said  
distal end surface of said hollow side panel section, which is on the opposite side of the hollow  
sheathing section.

~~said second diagonal rib formed within the other of said two hollow projecting~~  
~~sections is formed axisymmetrical to said diagonal rib formed within said projecting section~~  
~~provided on said sheathing sections, with a line as a symmetric axis which is parallel to said~~  
~~sheathing section and passing an intermediate point between said first diagonal rib formed within~~  
~~said projecting section provided on said sheathing section and said second diagonal rib formed~~  
~~within the other of said two hollow projecting sections,~~

~~a hollow portion of said hollow side panel section and hollow~~  
~~portions of said two hollow projecting sections are connected while each of said connected~~  
~~hollow portions are divided by said diagonal ribs.~~

2-3. Canceled.

4. (Previously presented) The form panel for placing concrete according to claim 1, wherein said sheathing section and said side panel sections are formed by integrating two panels and a plurality of long reinforcing ribs connecting these panels.

5. Canceled.

6. (Previously presented) The form panel for placing concrete according to claim 1, wherein said two hollow projecting sections are made of a soft resin or a semi hard resin.

7. (Previously presented) The form panel for placing concrete according to claim 1, wherein notches which are orthogonal to the longitudinal direction of said two hollow projecting sections are formed in the same position in each of said two hollow projecting sections.

8. (Previously presented) The form panel for placing concrete according to claim 1, wherein a hollow reinforcing panel section which is parallel to said side panel sections is provided on an opposite side of said sheathing section to said concrete placing surface of said sheathing section.

9. (Previously presented) The form panel for placing concrete according to claim 1, wherein said sheathing section is transparent or semitransparent.

10. (Previously presented) The form panel for placing concrete according to claim 1, wherein said form panel is configured to form spaces between adjacent form panels for conserving leaked concrete, said spaces being formed by setting outer surfaces of said two hollow projecting sections in abutting contact with the outer surfaces of two other hollow projecting sections which extend in a vertical direction provided on both side edges of the outside surfaces of the side panel sections of adjacent form panels for placing concrete.

11. Canceled.